

RP Strike-6" & RP 62"

variant Can-Am Commander

Standard Configurations




Strike-C

- High-Capacity, Multi-Modal Tactical Payload Flatbed Assembly
 - High-Load Tactical Team Standoff Nerf Bar Assembly/Rock Slider with Stow and Lock Mode for Air Transport
- 3. Tactical Assault Push Bumper with Strut Integrated Payload Track System and Aerial Transport Tie-downs
- 4. Multi-Modal Tailgate System for Multiple Tactical Payload Track Configurations and optional MEDEVAC integration (M4)
- 5. Rear Push Bumper Assembly with Aerial Transport Tie-downs
- 6. MSI Defense Passive Suspension Shocks
- 7. RP SOF Series II 12-Ply Run-Flat Tire, Black, 26x9x12
- 8. RP Fatigue Mitigation Warfighter MOLLE Tactical Seat System (1000 Denier CORDURA)
- 9. RP Hard Armor Coating

C2 (Command and Control)

- Tactical Assault Push Bumper with Strut Integrated Payload Track System and Aerial Transport Tie-downs
- 2. Flat Black Exterior
- 3. RP Fatigue Mitigation Warfighter MOLLE Tactical Seat System (1000 Denier CORDURA)
- 4. RP SOF Series II 12-Ply Run-Flat Tire, Black, 26x9x12



supplemental power management

7. MSI Defense

Passive
Suspension
Shocks



OPTIONS

- Severe Duty 4-Point Retractable Harness Kit with Quick Release Rotary Buckle
- 2. RP Modular Ammo/Fuel Can/Payload Assemblies
- 3. RP Beadlock Wheel, Black, CC 14x7 [4+3] 4/137
- 4. RP SOF Series II 12-Ply Run-Flat Tire, Black, 26x9x14
- 5 RODS Rear Open Differential System (selectable)
- 6. RP Keyless Anti-Theft Ignition System
- 7. Additional HID Light Illumination
- 8. Blackout/Infrared Capability for NVG Operations
- Quick Release Articulating Roll Cage Assembly for Internal Aerial Transport
- 10. RP Modular Front Cargo Rack Assembly
- 11. MSI Defense Series Shock packages:
 - 2.5" Piggyback Shaft Adjustable Compression Shocks (passive)
 - 2.5" ProTune Semi-Active Shock System w/Terrain selection shock Tuning Control (patent pending)
 - Optional Color Display with Night Vision or Smart Keypad

CAN-AM VEHICLE CAPABILITIES

- 1. 976 CC, 85 hp, V-Twin, Liquid-Cooled Engine with EFI
- 2. CVT, Sub-Transmission with High, Low, Park, Neutral & Reverse.
- 3. Selectable 2WD/4WD Shaft Driven with Visco-Lok Auto-Locking Front Differential
- 4. 51 mm diameter, High-Strength Steel, ROPS-Approved

DRY WEIGHT	1,497 – 1,597 lb
DIMENSIONS	118 (L) x 58.6 (W) x 72 in (H) and 118 (L) x 58.6 (W) x 60 in (H) with Retracted Roll Cage
WHEELBASE	75.8 in
GROUND CLEARANCE	11 in
FUEL CAPACITY	10 gal
TOWING CAPACITY	1,500 lb





www.MILITARYATV.com

World of Powersports

Cage:8ALC7 DUNS: 025393588 2635 N 22nd St, Decatur, IL 62526

Direct: 213-935-0840 FAX: 217-233-8384

email: mikej@worldofpowersports.com