



Catalog for Bridgelux LED Coolers



Mingfa Tech Manufacturing Limited
Tel: +86-769-33252828 +86-769-33251919
E-fax: +86-(020)28819702 ext:22122
Email:sales@mingfatech.com
[Http://www.heatsinkled.com](http://www.heatsinkled.com)
[Http://www.mingfatech.com](http://www.mingfatech.com)

Version-2015

EtraLED LED Cooling Series

EtraLED-BRI-4850

Bridgelux Modular Star LED Heat Sink
 Vero 10, Vero 13, ES Star array with direct mounting
 V6, V8 with LED holder
 ES Rectangle array direct mounting or with Zhaga LED holder
 ø48mm – h50mm - Rth 4.2° C/W.
 Cooling performance 600 - 1600 lm.



EtraLED-BRI-4880

Bridgelux Modular Star LED Heat Sink
 Vero 10, Vero 13, ES Star array with direct mounting
 V6, V8 with LED holder
 ES Rectangle array direct mounting or with Zhaga LED holder
 ø48mm – h80mm - Rth 3.6° C/W.
 Cooling performance 800 - 2000 lm.



EtraLED-BRI-7050

Bridgelux Modular Star LED Heat Sink
 Vero 10, Vero13, Vero 18, ES Star array with direct mounting
 V8 with LED holder
 ES Rectangle array direct mounting or with Zhaga LED holder
 ø70mm – h50mm - Rth 2.1° C/W
 Cooling performance 900 - 2800 lm



EtraLED-BRI-7080

Bridgelux Modular Star LED Heat Sink
 Vero 10, Vero13, Vero 18, ES Star array with direct mounting
 V8 with LED holder
 ES Rectangle array direct mounting or with Zhaga LED holder
 ø70mm – h80mm - Rth 1.75° C/W
 Cooling performance 1200 - 3300 lm



EtraLED-BRI-8550

Bridgelux Modular Star LED Heat Sink
 Vero 10, Vero13, Vero 18, ES Star array with direct mounting
 ES Rectangle array direct mounting or with Zhaga LED holder
 ø85mm – h50mm - Rth 1.5° C/W
 Cooling performance 1800 - 4200 lm




EtraLED-BRI-8580

Bridgelux Modular Star LED Heat Sink
 Vero 10, Vero13, Vero 18, ES Star array with direct mounting
 ES Rectangle array direct mounting or with Zhaga LED holder.
 ø85mm – h80mm - Rth 1.3° C/W
 Cooling performance 2000 - 4700 lm



EtraLED-BRI-9650

Bridgelux Modular Star LED Heat Sink
 RS array with direct mounting
 ES Rectangle array direct mounting or with Zhaga LED holder
 ø96mm – h50mm - Rth 1.2° C/W
 Cooling performance 1500 - 4500 lm



EtraLED-BRI-9680

Bridgelux Modular Star LED Heat Sink
 RS array with direct mounting
 ES Rectangle array direct mounting or with Zhaga LED holder
 ø96mm – h80mm - Rth 0.9° C/W
 Cooling performance 2000 - 5800 lm




EtraLED-BRI-11050

Bridgelux Modular Star LED
Heat Sink
RS array with direct mounting
ES Rectangle array direct mounting
or with Zhaga LED holder
ø110mm – h50mm - Rth 1.1° C/W
Cooling performance 2500 - 6000 lm



EtraLED-BRI-11080

Bridgelux Modular Star LED
Heat Sink
RS array with direct mounting
ES Rectangle array direct mounting
or with Zhaga LED holder
ø110mm – h80mm - Rth 0.9° C/W
Cooling performance 3300 - 7400 lm




EtraLED-BRI-13050

Bridgelux Modular Star LED
Heat Sink
Vero 29 with direct mounting
ES Rectangle LED arrays mounting
with Zhaga LED holder
ø130mm – h50mm - Rth 0.9° C/W
Cooling performance 3000 - 7200 lm



EtraLED-BRI-13080

Bridgelux Modular Star LED
Heat Sink
Vero 29 with direct mounting
ES Rectangle LED arrays mounting
with Zhaga LED holder
ø130mm – h80mm - Rth 0.7° C/W
Cooling performance 4000 - 9800 lm



GooLED LED Cooling Series

GooLED-BRI-4830

Bridgelux Modular Pin Fin LED
Heatsink
Vero10,Vero13, with direct mounting
ES Rectangle array with Zhaga LED
holder
ø48mm – h30mm - Rth 5.7° C/W
Cooling performance 400 - 1200 lm



GooLED-BRI-4850

Bridgelux Modular Pin Fin LED
Heatsink
Vero10,Vero13,with direct mounting
ES Rectangle array with Zhaga LED
holder
ø48mm – h50mm - Rth 4.2° C/W
Cooling performance 500 - 1600 lm



GooLED-BRI-4868

Bridgelux Modular Pin Fin LED
Heatsink
Vero13, Vero18 with direct mounting
ES Rectangle array with Zhaga LED
holder
ø48mm – h68mm - Rth 3.7° C/W
Cooling performance 900 - 3000 lm



GooLED-BRI-5830

Bridgelux Modular Pin Fin LED
Heatsink
Vero10, Vero13 with direct mounting
ES Rectangle array with Zhaga LED
holder
ø58mm – h30mm - Rth 4.5° C/W
Cooling performance 500 - 1500 lm



GooLED-BRI-5850

Bridgelux Modular Pin Fin LED Heatsink
Vero10, Vero13 ES Star array with direct mounting V6, V8 with LED holder
ES Rectangle array with Zhaga LED holder
ø58mm – h50mm - Rth 3.3° C/W
Cooling performance 600 - 1900 lm



GooLED-BRI-6830

Bridgelux Modular Pin Fin LED Heatsink
Vero10, Vero 13 with direct mounting ES Rectangle array with Zhaga LED holder
ø68mm – h30mm - Rth 3.5° C/W
Cooling performance 700 - 1800 lm



GooLED-BRI-6850

Bridgelux Modular Pin Fin LED Heatsink
Vero10, Vero13, Vero18, ES Star array with direct mounting V6, V8 with LED holder
ES Rectangle array with Zhaga LED holder
ø68mm – h50mm - Rth 2.7° C/W
Cooling performance 900 - 2400 lm



GooLED-BRI-6860

Bridgelux Modular Pin Fin LED Heatsink
Vero10, Vero13, Vero18, ES Star array with direct mounting V6, V8 with LED holder
ES Rectangle array with Zhaga LED holder
ø68mm – h60mm - Rth 2.5° C/W
Cooling performance 1200 - 3000 lm



GooLED-BRI-7830

Bridgelux Modular Pin Fin LED Heatsink
Vero10, Vero13, Vero18, ES Star array with direct mounting V6, V8 with LED holder
ES Rectangle array with Zhaga LED holder
ø78mm – h30mm - Rth 2.7° C/W
Cooling performance 700 - 2400 lm



GooLED-BRI-7850

Bridgelux Modular Pin Fin LED Heatsink
Vero10, Vero13, Vero18, ES Star array with direct mounting V6, V8 with LED holder
ES Rectangle array with Zhaga LED holder
ø78mm – h50mm - Rth 2.1° C/W
Cooling performance 1200 - 3200 lm



GooLED-BRI-11050

Bridgelux Modular Pin Fin LED Heatsink
Vero 13, Vero18 with direct mounting ES Rectangle array with Zhaga LED holder
ø110mm – h50mm - Rth 1.3° C/W
Cooling performance 1500 - 5000 lm



GooLED-BRI-11080

Bridgelux Modular Pin Fin LED Heatsink
Vero 13, Vero18 with direct mounting ES Rectangle array with Zhaga LED holder
ø110mm – h80mm - Rth 1.0° C/W
Cooling performance 2500 - 6500 lm



SimpoleD LED Cooling Series

SimpoleD-BRI-5850

Bridgelux Modular LED Star cooler
Design for Bridelux Vero-10 ES Star
Array V8 and V6 COB LED arrays.
Direct mounting or with Zhaga LED
holder.
ø58mm – h50mm - Rth 4.1° C/W
Cooling performance 500 - 1300 lm



SimpoleD-BRI-5870

Bridgelux Modular LED Star cooler
Design for Bridelux Vero-10 ES Star
Array V8 and V6 COB LED arrays
Direct mounting or with Zhaga LED
holder.
ø58mm – h70mm - Rth 3.2° C/W
Cooling performance 700 - 2000 lm



SimpoleD-BRI-8150

Bridgelux Modular LED Star cooler
Design for Bridelux ES-Rectangle
Vero-10 ES Star Array V8 and V6 COB
LED arrays.
Direct mounting or with Zhaga LED
holder.
ø81mm – h50mm - Rth 1.9° C/W
Cooling performance 1000 - 3200 lm



SimpoleD-BRI-8180

Bridgelux Modular LED Star cooler
Design for Bridelux ES-Rectangle
Vero-10 ES Star Array V8 and V6 COB
LED arrays .
Direct mounting or with Zhaga LED
holder.
ø81mm – h80mm - Rth 1.6° C/W
Cooling performance 1500 - 3800 lm



SimpoleD-BRI-11750

Bridgelux Modular LED Star cooler
Design for Bridelux ES-Rectangle
Vero-10 ES Star Array Vero13 Vero18
V8 and V6 COB LED arrays.
Direct mounting or with Zhaga LED
holder.
ø117mm – h50mm - Rth 1.0° C/W
Cooling performance 2000 - 6000 lm




SimpoleD-BRI-11780

Bridgelux Modular LED Star cooler
Design for Bridelux ES-Rectangle
Vero-10 ES Star Array Vero13 Vero18
V8 and V6 COB LED arrays.
Direct mounting or with Zhaga LED
holder.
ø117mm – h80mm - Rth 0.82° C/W
Cooling performance 2500 - 7300 lm




SimpoleD-BRI-13550

Bridgelux Modular LED Star cooler
Vero 10, Vero 13, Vero 18, Vero 29
with direct mounting ES Rectangle
array with Zhaga LED holder.
ø135mm – h50mm - Rth 0.82° C/W
Cooling performance 2000 - 7300 lm



SimpoleD-BRI-13580

Bridgelux Modular LED Star cooler
Vero 10, Vero 13, Vero 18, Vero 29
with direct mounting ES Rectangle
array with Zhaga LED holder.
ø135mm – h80mm - Rth 0.71° C/W
Cooling performance 3000 - 9000 lm



SimpoleD-BRI-16050

Bridgelux Modular LED Star cooler
Vero 10, Vero 13, Vero 18, Vero 29
with direct mounting ES Rectangle
array with Zhaga LED holder
Ø160mm – h50mm - Rth 0.7° C/W
Cooling performance 3000 - 9000 lm



SimpoleD-BRI-160100

Bridgelux Modular LED Star cooler
Vero 10, Vero 13, Vero 18, Vero 29
with direct mounting ES Rectangle
array with Zhaga LED holder
Ø160mm – h100mm – Rth 0.56° C/W
Cooling performance 4000-11000 lm



SimpoleD-BRI-160150

Bridgelux Modular LED Star cooler
Vero 10, Vero 13, Vero 18, Vero 29
with direct mounting ES Rectangle
array with Zhaga LED holder
Ø160mm – h150mm - Rth 0.5° C/W
Cooling performance 5000-12000 lm



.....End.....