

# Water from Air AWG

40 Liters/10.56 Gallons Per Day

*4th Generation* Residential Units



pan**L**bilt GLOBAL

[www.PanLbilt.com](http://www.PanLbilt.com)

# Water from Air AWG

## 40 Liter /10.56 Gal *4th Generation* Residential Units

### Features and Benefits

- ⇒ Produces Fresh Drinking water that meets or exceeds World Health Organization (WHO) standards
- ⇒ Plugs into in-house On-Grid electrical outlets
- ⇒ Can be powered via Off-Grid solar energy
- ⇒ Easy user-friendly installation of replacement filters
- ⇒ Uses Green technology that eliminates plastic bottles
- ⇒ Mitigates transportation costs; fresh drinking water is produced *on-site* solely from the atmosphere
- ⇒ Eliminates dependence upon municipal infrastructure and health risks from degraded pipes subject to lead or bacteria
- ⇒ Greatly reduces cost of liters/gallons
- ⇒ Enables Rapid Return on Investment (ROI) of Capital Costs

pan**L**bilt GLOBAL

[www.PanLbilt.com](http://www.PanLbilt.com)

**Water from Air AWG**  
**40 Liters/10.56 Gallons Per Day**  
**4th Generation Residential Units**

**AWG 40L BX**

**Cold Water only**  
**5 Stage Water Filtration**  
**Touch Screen Control**

**AWG 40L MX**

**Includes Child lock feature to ensure safety**  
**Hot and Cold Water Options**  
**Touch Screen Control & Indicators**  
**5 Stage Water Filtration**

**AWG 40L PX**

**Power Failure Indicator**  
**Child lock feature to ensure safety**  
**Hot, Cold & Soda Water Options**  
**Touch Screen Control & Indicators**  
**Wi-Fi enabled & Mobile App Control**  
**5 Stage Water Filtration**

**pan**L**bilt** GLOBAL

[www.PanLbilt.com](http://www.PanLbilt.com)

# Water from Air AWG

## 20 Liter /5.28 Gal 4th Generation Residential

### Technical Specifications

Power: **110V/60 cycles US, 220V/50 cycles European**

Power Consumption: **700W per hour/ 16.8 kW per day**

Rated Current: **3.5 Amps**

Working Temperature: **5° C/41° F to 35° C/95° F**

Dehumidify Capacity (30°C/86°F at 80% RH): **420 Liters/10.56 Gallons per day**

Full Water Quantity: **5.5 L/1.45 Gal**

Air Circulation: **450 m<sup>3</sup>/hr.**

Control Type: **Electronic**

Status Indicator: **Buker full signal light**

Recommended room size: **50 m<sup>2</sup>/538 SF**

Noise: **≤60dB**

Refrigerant Charge: **R410A**

Dimensions: **16.9"/42.9cm L x 15.75"/40cm W x 42.9"/108.9cm H**

Weight: **55 kg/121.2 lbs**

# Units per 40-foot Container: **240**

**pan**L**bilt** GLOBAL

[www.PanLbilt.com](http://www.PanLbilt.com)